



	Catalog Page No.	<b>Finished Widths</b>	Put-Up (Lengths)	Cut Yardage	Weight (Oz.)	Finish (Coating)	Colors	Mildew Resistant
Fabrics								
Arlon Colorkote	6	7′	10yd, 25yd, 50yd	Yes	21 oz.	Eradicable Premium Ink	20 Solids	Yes
Arlon Eradicolor	6	7'	10yd, 25yd, 50yd	Yes	18 oz.	Eradicable Premium Ink	15 Solids	Yes
Arlon Wide Flex 6	7	4'-6", 6'-6", 8'-6", 10'-6", 12'-6", & 16'-4"	105', 165'	Yes	18 oz.	Gloss	White	n/a
Cooley Brite	9	6-6″	10yd, 25yd, 50yd	No	20 oz.	PVC	20 Solids	Yes
Cooley Brite II	9	6-6″	10yd, 25yd, 50yd	No	20 oz.	PVC	20 Solids	Yes
Cooley Brite Lite	10	6-6″	10yd, 25yd, 50yd	No	16 oz.	PVC	18 Solids	Yes
Cooley Seamless SM42	7	8'-6", 10'-6", 12'-6" & 196"*	150'& 165'*	Yes	20 oz.	PVC	White	Yes
Cooley Weathertyte	8	74″	50yd	Yes	16 oz.	PVC	16 Regular / 4 Premium	Yes
Cooley Weathertyte Lite	8	74″	50yd	Yes	11 oz.	PVC	5 Regular / 2 Premium	Yes
Decorline	14	54″	65yd	Yes	8 oz.	Fluorocarbon/ Resin	19 Solids / 6 Patterns	Yes
Holiday	10	62″	45yd	Yes	12.95 oz.	Acrylic	6 Regular / 3 Premium	Yes
Recacril Design Line	12-13	47", 60" & 98"	65yd	Yes	9 oz.	Fluorocarbon/ Resin	59 Solids / 79 Stripes	Yes
RecWater	14	60″	65yd	Yes	17.4 oz	One Side PVC Coated	10 Solids	Yes
RecScreen 4000P	14	118″	27yd	Yes	15.17 oz.	Antibacterial & Lead Free	9 Patterns	Yes
RecScreen 5000P	14	118″	27yd	Yes	14.75 oz.	Antibacterial & Lead Free	10 Patterns	Yes
RecScreen 6000P	14	118″	27yd	Yes	17.84 oz.	Antibacterial & Lead Free	13 Patterns	Yes
Seaquest	15	54″	Flat: 40yds / Pleated: 10-15yds	Yes	32 oz.	n/a	29 Solids	Yes
Sunsure Plus	15	61″	60yd	Yes	14.3 oz.	PVC	6 Solids	Yes
Valmex Nautica Light	11	86.5″	32yd	Yes	8.2 oz.	One Side PVC Coated	9 Solids	Yes
Valmex Nautica Light (Coated Both Sides)	11	86.5″	32yd	Yes	12.7 oz.	Both Sides PVC Coated	8 Solids	Yes
Valmex Nautica Linen	11	84.5″	32yd	Yes	11.8 oz.	One Side PVC Coated	2 Solids	Yes
Valmex Nautica Heavy	11	86.5″	32yd	Yes	13.1 oz.	One Side PVC Coated	6 Solids	Yes

4

To view more information on any one of these products, turn to the appropriate pages in our catalog or call today for more information!

\*Cooley Seamless SM42 196" x 165' is available in a Matte finish only.

	Eradicable	0	Translusant	FR	Heat Sealable	Limited	UV	Other Uses
		Opaque	Translucent	ГК	Sealable	Warranty	00	Other Oses
Fabrics		1			1	1	1	1
Arlon Colorkote	Yes	No	Yes	Yes	Yes	10 Years	1000 Hours	Awning / Sign
Arlon Eradicolor	Yes	No	Yes	Yes	Yes	6 Years	n/a	Awning / Sign
Arlon Wide Flex 6	No	No	Yes	Yes	Yes	6 Years	2000 Hours	Awning / Sign
Cooley Brite	Yes	No	Yes	Yes	Yes	8 Years	n/a	Awning / Sign
Cooley Brite II	Yes	No	Yes	Yes	Yes	10 Years	n/a	Awning / Sign
Cooley Brite Lite	Yes	No	Yes	Yes	Yes	8 Years	n/a	Awning / Sign
Cooley Seamless SM42	No	No	Yes	Yes	Yes	5 Years	n/a	Awning / Sign
Cooley Weathertyte	No	No	No	Yes	Yes	8 Years	n/a	Awning / Marine
Cooley Weathertyte Lite	No	No	No	Yes	Yes	5 Years	n/a	Awning / Marine
Decorline	No	Yes	No	Yes	Yes	3 Years	n/a	Marine
Holiday	No	Yes	No	Yes	Yes	5 Years	n/a	Awning / Marine
Recacril Design Line	No	Yes	No	No	Yes	5 Years	1500+ Hours	Marine
RecWater	No	Yes	No	No	Yes	5 Years	n/a	Marine
RecScreen 4000P	No	No	Yes	Yes	Yes	3 Years	n/a	Sunscreens / Windscreens Patio Furniture
RecScreen 5000P	No	No	Yes	Yes	Yes	3 Years	n/a	Sunscreens / Windscreens Patio Furniture
RecScreen 6000P	No	No	Yes	Yes	Yes	3 Years	n/a	Sunscreens / Windscreens Patio Furniture
Seaquest	No	No	No	Yes	n/a	n/a	1000 Hours	Marine
Sunsure Plus	No	No	No	Yes	Yes	3 Years	1200 Hours	Sunscreen / Marine
Valmex Nautica Light	No	No	Varies	Yes	Yes	n/a	n/a	Marine
Valmex Nautica Light (Coated Both Sides)	No	No	Varies	Yes	Yes	n/a	n/a	Marine
Valmex Nautica Linen	No	No	Varies	Yes	Yes	n/a	n/a	Marine
Valmex Nautica Heavy	No	No	Varies	Yes	Yes	n/a	n/a	Marine

To view more information on any one of these products, turn to the appropriate pages in our catalog or call today for more information!







# **ARION SIGN**TECH

# **COLORKOTE<sup>®</sup> TC**

**10-Year Warranty** 

Colorkote TC is a premium **21oz.** eradicable, flexible, vinyl substrate coated with premium ink and covered with our advanced FX outer protective coating. **Available in 20 popular colors**, this pre-decorated flexible substrate is created for the sign and awning industries for backlit graphic applications with solid background coverage. Designed to be eradicated using Signtech Eradicator.

Put-Up (Lengths) Finished Widths	10yds, 25yd 7'	ls, 50yds & Cut Yarda	ge
Base Fabric / Type	Reinforced Vinyl Subs	strate	
Finish (Coating)	Eradicable Premium I	nk	
Weight	21 oz.		
Mildew Resistant	Yes	Heat Sealable	Yes
Eradicable	Yes	Translucent	Yes
Opaque	No	Fire Resistant	Yes
Limited Warranty	10 years		
Other Uses:	Awning & Sign		
Specifications	Test Method	Test Results	
UV Resistance	ASTM D4329-92	1000 Hours	
Abrasion	n/a	n/a	
Hydrostatic	n/a	n/a	
Puncture Strength	n/a	n/a	
Tear Strength	n/a	n/a	
Tensile Strength	ASTM D1593-89	178 lbf warp, 159 lbf fil	1
Tensile Strength		.8mm at 100°C for 30 r	nin
Shrinkage	ASTM D1593-89	.011111 at 100 C 101 50 1	

	Color	Colorkote SKU	Eradicolor SKU
1090	Yellow	TC1090	
2016	Dark Yellow	TC2016	ER2016
2020	Burgundy	TC2020	ER2020
2025	Black (Opaque)	TC2025	ER2025
2037	Lt. Yellow	TC2037	ER2037
2108	Holly Green	TC2108	ER2108
2114	Dark Blue	TC2114	ER2114
2119	Orange	TC2119	ER2119
2146	lvory	TC2146	
2260	Cherise	TC2260	

NEPCO also offers Special Colorkote TC Program Colors! These special colors are only available in cut yardage only.

Color	SKU
Dunkin Donuts™ Burgundy	STDD3-BURGUNDY
Dunkin Donuts™ Brown	STDD8-BROWN
Dunkin Donuts™ Orange	STDD9-ORANGE
Metro PCS™ Purple	TC6-140CUT

# ERADICOLOR

6-Year Warranty

ERADICOLOR is an **18 oz.** intermediate-grade, eradicable, flexible, vinyl substrate. **Available in 15 popular colors**, this value-priced flexible substrate can be used anywhere where a medium-term signage/awning solution is needed. Stretch your dollar with ERADICOLOR. Designed to be eradicated using Simulated Eradicator Signtech Eradicator.

Put-U Finis	Up (Lengths) hed Widths	10yd 7'	s, 25yds, 5	0yds &	Cut Yarda	ge
Base Fa	abric / Type	Reinforced V	inyl Substrate	e		
Finish	(Coating)	Eradicable P	remium Ink			
Weigh	t	18 oz.				
Mildev	v Resistant	Yes		Heat Sea	lable	Yes
Eradic	able	Yes		Transluc	ent	Yes
Opaqu	ie	No		Fire Resi	stant	Yes
Limite	d Warranty	6 years				
Other	Uses:	Awning & Si	gn			
Specifi	ications	Test Method	l	Test Res	ults	
UV Re	esistance	n/a		n/a		
Abrasi	on	n/a		n/a		
Hydro	static	n/a		n/a		
Punctu	ire Strength	n/a		n/a		
Tear St	rength	n/a		12 lbf wa	rp, 8 lbf fill	
Tensile	Strength	n/a		180 lbf/ii	1 warp, 120 lb	f/in fill
Shrink	age	n/a		n/a		
Stretch	L	n/a		n/a		
	Color		Colorkote	SKU	Eradicol	or SKU
2283	Red		TC2283		ER2283	

2283         Red         TC2283         ER2283           2410         Medium Red         TC2410           2510         Red         TC2510         ER2510           2662         Tomato Red         TC2662         ER2662           2870         Royal Blue         TC2930         ER2870           2930         Blue         TC3220         ER200           4048         Dark Green         TC44048         ER4048           4355         Lt. Green         TC4355         ER4355           5019         Teal Blue         TC5019         ER5019					
International         TC210           2510         Red         TC2510         ER2510           2662         Tomato Red         TC2662         ER2662           2870         Royal Blue         TC2870         ER2870           2930         Blue         TC2930         ER2930           3220         Turquoise         TC3220            4048         Dark Green         TC4048         ER4048           4355         Lt. Green         TC4355         ER4355	2283	Red	TC2283	ER2283	
2662         Tomato Red         TC2662         ER2662           2870         Royal Blue         TC2870         ER2870           2930         Blue         TC2930         ER2930           3220         Turquoise         TC3220         ER4048           4048         Dark Green         TC4048         ER4048           4355         Lt. Green         TC4355         ER4355	2410	Medium Red	TC2410		
2870         Royal Blue         TC2870         ER2870           2930         Blue         TC2930         ER2930           3220         Turquoise         TC3220           4048         Dark Green         TC4048         ER4048           4355         Lt. Green         TC4355         ER4355	2510	Red	TC2510	ER2510	
2930         Blue         TC2930         ER2930           3220         Turquoise         TC3220           4048         Dark Green         TC4048         ER4048           4355         Lt. Green         TC4355         ER4355	2662	Tomato Red	TC2662	ER2662	
3220         Turquoise         TC3220           4048         Dark Green         TC4048         ER4048           4355         Lt. Green         TC4355         ER4355	2870	Royal Blue	TC2870	ER2870	
4048         Dark Green         TC4048         ER4048           4355         Lt. Green         TC4355         ER4355	2930	Blue	TC2930	ER2930	
4355 Lt. Green TC4355 ER4355	3220	Turquoise	TC3220		
	4048	Dark Green	TC4048	ER4048	
5019         Teal Blue         TC5019         ER5019	4355	Lt. Green	TC4355	ER4355	
	5019	Teal Blue	TC5019	ER5019	



6

# **NEED A SAMPLE OF SOME FABRIC?** ~ NO SWEAT!

NEPCO Also offers sample cards for all of our Awning Fabric Products! Call today for a free swatch!

# WIDE FLEX 6

stability for great tensioning without sag.

# **TECHNICAL DATA**

Put-Up (Lengths) Finished Widths	Lengths)         105, 165' & Cut Yardage           Widths         4'-6", 6'-6", 8'-6", 10'-6", 12'-6" & 16'-4"		Specifications	Test Method	Test Results	
i monea wiamo	1 0,0 0,0 0,10 0,12 0 0,10 -4			UV Resistance	ASTM D4329-05	2000 Hours
Base Fabric / Type	Polymetric PVC Viny	1		Abrasion	n/a	n/a
				Hydrostatic	n/a	n/a
	18 oz.			Puncture Strength	n/a	n/a
Mildew Resistant	n/a	Heat Sealable	Yes		ASTM D1593-99	68 lbs warp, 57 lbs fill
Eradicable	No	Translucent	Yes	Tensile Strength	ASTM D1593-99	301 lbs warp, 290 lbs fill
Opaque	Yes	Fire Resistant	Yes	Shrinkage	n/a	n/a
Limited Warranty	6 years			Stretch	n/a	n/a
Other Uses:	Awning & Sign					

	4' - 6" SKU**	6' - 6" SKU	8' - 6" SKU	10'-6" SKU	12'- 6" SKU	16'-4" SKU
By the Roll (105')	A-FLX6-4'X105	A-FLX6-6X105	A-FLX6-8X105	A-FLX6-10X105	A-FLX6-12X105	A-FLX6-16X105
By the Roll (164')	A-FLX6-4X164	A-FLX6-6X164	A-FLX6-8X164	A-FLX6-10X164	A-FLX6-12X164	A-FLX6-16X164
By the Yard	A-FLX6-4'-CUT	A-FLX6-6'-CUT	A-FLX6-8'-CUT	A-FLX6-10'-CUT	A-FLX6-12'-CUT	A-FLX6-16'-CUT

\*\*54 inches - Special size for smaller printers.

# Cooley

# **COOLEY SEAMLESS SM42**

Cooley Seamless SM42, 20oz. Flexible Backlit Substrate, features excellent lay-flat properties and a fine scrim which is virtually invisible.

Put-Up (Lengths)         150', 165'** & Cut Yardage           Finished Widths         8'-6", 10'-6", 12'-6" & 196"**				Specifications	Test Method	Test Results	
i moneu vviduio	0 0,10 0	,12 0 <b>Q</b> 190		UV Resistance	n/a	n/a	
Base Fabric / Type	Polyester			Abrasion	n/a	n/a	
	PVC			Hydrostatic	n/a	n/a	
Weight	20 oz.			Puncture Strength	ASTM D1204	35 lbs	
Mildew Resistant	Yes	Heat Sealable	Yes		ASTM D1004 (mod)	50 lbs warp, 30 lbs fill	
Eradicable	No	Translucent	Yes	Tensile Strength	ASTM D751-A Grab	225 lbs warp, 150lbs fill	
Opaque	No	Fire Resistant	Yes	Shrinkage	ASTM D1204	< 1.5%	
Limited Warranty	5 years			Stretch	n/a	n/a	
Other Uses:	Awning & Sign						

	8' - 6" SKU	10'- 6" SKU	12'-6" SKU	196" SKU**
By the Roll (150′)	0020C120AI	0020C126AI	0020C150AI	
By the Roll (165′)**				0020C19655I
By the Yard	0020C102AI-CUT	0020C126AI-CUT	0020C150AI-CUT	0020C19655I-CUT

\*\*196" x 165" - Available in a Matte finish only.



# Arlon's **18oz**. best wide width white flexible substrate with a 6-year outdoor durability. Decorate with Arlon's 2-mil Translucent Series 2500 or digital print with eco-solvent or UV inks. With its low shrink, high strength polyester scrim, Wide Flex 6 has good dimensional





# Cooley Meathertyte

Weathertyte is a **16oz.** technically advanced waterproof awning fabric, which offers the luxurious look and feel of a woven fabric but has all the benefits of a high performance composite vinyl. Weathertyte can be decorated with conventional techniques & all colors can also be easily digitally printed.

Its also the perfect fabric for applications where protection from the environment is essential, such as boat covers and bimini tops, flags, awnings, banners and so much more.

Put-Up (Lengths) Finished Widths	50yds, & Cu 74"	t Yardage	
Base Fabric / Type	Polyester		
Finish (Coating)	PVC		
Weight	16 oz.		
Mildew Resistant	Yes	Heat Sealable	Yes
Eradicable	No	Translucent	No
Opaque	No	Fire Resistant	Yes
Limited Warranty	8 years		
Other Uses:	Awning & Marine		
Specifications	Test Method	Tast Desults	

Specifications	Test Method	Test Results
UV Resistance	n/a	n/a
Abrasion	ASTM D4157	60,000+ Cycles
Hydrostatic	ASTM D751-A	330 psi
Puncture Strength	ASTM D751	50 lbs
Tear Strength	ATSM D751-B (mod)	55 lbs warp, 57 lbs fill
Tensile Strength	ASTM D751-A Grab	257 lbs warp, 149 lbs fill
Shrinkage	n/a	n/a
Stretch	n/a	n/a
		••••••

Color	Weathertyte SKU	Weathertyte Lite SKU
Beige	WT-76BGE	
Black	WT-76BK	WTL-74DS-BLK
Blue	WT-76BL	WTL-74DS-BLU
Burgundy *	WT-76BU	WTL-74DS-BUR
Charcoal	WT-76CHR	
Chocolate Brown	WT-76BWN	
Coral	WT-76COR	
Dark Blue	WT-76DBL	
Dark Red *	WT-76DRD	WTL-74DS-DRD
Forest Green	WT-76FGR	WTL-74DS-FGR

\*Indicates a Premium Color.







**Cooley** Weathertyte *Lite* 

Weathertyte, but its lighter weight offers easier handling. With its **11oz.** lightweight scrim, it still makes the

perfect fabric for applications where protection from the environment is key, such as boat covers and bimini tops,

Just like Weathertyte it offers the luxurious look and feel of a woven fabric but has all the benefits of a high performance

50yds & Cut Yardage

Heat Sealable

Fire Resistant

Translucent

Test Results

60,000+ Cycles

50 lbs warp, 45 lbs fill

230 lbs warp, 150 lbs fill

WTL-74DS-LN

Weathertyte Lite SKU

WTL-74DS-WHT

n/a

300 psi

50 lbs

n/a

n/a

Yes

No

Yes

Weathertyte Lite offers the same overall benefits of

74"

Polyester

PVC

11 oz.

Yes

No

No

n/a ASTM D4157

n/a

n/a

5 years

Awning & Marine

Test Method

ASTM D751-A

ASTM D751-B (mod)

ASTM D751-A Grab

Weathertyte SKU

WT-76GR WT-76LN

WT-76MVE

WT-76PLT

WT-76RD WT-76SLT

WT-76SF WT-76TRC

WT-76WT

WT-76YL

ASTM D751

flags, awnings, banners and so much more.

composite vinyl.

**TECHNICAL DATA** Put-Up (Lengths)

Finished Widths

Base Fabric / Type

Finish (Coating)

Mildew Resistant

Limited Warranty

Weight

Eradicable

Opaque

Other Uses:

Specifications

UV Resistance

Abrasion

Hydrostatic

Tear Strength

Shrinkage

Stretch

Color

Green

Linen

Mauve Platinum

Red \*

Slate Sunflower

White Yellow

8

Terracotta

Tensile Strength

Puncture Strength



# **COOLEY-BRITE**<sup>®</sup>

Cooley's original backlit sign and awning material, Cooley-Brite **20oz.** comes with an eight year warranty. This membrane features a scrim design that is nearly invisible to allow for maximum light diffusion, consistent translucency and brilliant eradicable colors in backlit signs and awnings. Cooley-Brite is treated with anti-wick, ultraviolet stabilizers, fungicides and whiteners for excellent color protection, durability and long life.

Put-Up (Lengths) Finished Widths	10yds, 25yds 6'-6"	& 50yds	
Base Fabric / Type	Polyester		
Finish (Coating)	PVC		
Weight	20 oz.		
Mildew Resistant	Yes	Heat Sealable	Yes
Eradicable	Yes	Translucent	Yes
Opaque	No	Fire Resistant	Yes
Limited Warranty	8 years		
Other Uses:	Awning & Sign		
Specifications	Test Method	Test Results	
UV Resistance	n/a	n/a	
Abrasion	n/a	n/a	
Hydrostatic	n/a	n/a	
Puncture Strength	ASTM D751	35 lbs	
Tear Strength	ASTM D1004 (mod)	50 lbs warp, 30 lbs fill	

	Color	Cooley Brite SKU	Cooley Brite II SK
0123	Sunflower	83-0123	83-C0123
0132	Bright Red	83-0132	83-C0132
0219	Pink	83-0219	83-C0219
0248	Plum	83-0248	83-C0248
0301	Mid Blue	83-0301	83-C0301
0355	Light Green	83-0355	83-C0355
0606	White	83-0606	83-C0606
2020	Burgundy	83-2020	83-C2020
2025	Black	83-2025	83-C2025
2037	Yellow	83-2037	83-C2037

ASTM D1204

n/a

Shrinkage

Stretch

< 1.5 %

n/a





# FABRIC COOLEY BRITE & BRITE II

# **COOLEY-BRITE<sup>®</sup> II**

This **20oz.**, flexible, eradicable, top-of-the-line sign and awning membrane possesses all the advantages of the colored Cooley-Brite and more. Cooley-Brite II features the added protection of Cooley's Coolthane<sup>®</sup> formulation, which enhances cleanability and extends the life of the product to ten years.

Put-Up (Lengths) Finished Widths	10yds, 25yds 6'-6"	& 50yds	
Base Fabric / Type	Polyester		
Finish (Coating)	PVC		
Weight	20 oz.		
Mildew Resistant	Yes	Heat Sealable	Yes
Eradicable	Yes	Translucent	Yes
Opaque	No	Fire Resistant	Yes
Limited Warranty	10 years		
Specifications	Test Method	Test Results	
opeemeations	lest method	Test Results	
UV Resistance	n/a	n/a	
UV Resistance Abrasion	n/a	n/a	
UV Resistance Abrasion Hydrostatic	n/a n/a	n/a n/a	
UV Resistance Abrasion Hydrostatic Puncture Strength	n/a n/a n/a	n/a n/a n/a	
UV Resistance	n/a n/a ASTM D751	n/a n/a n/a 35 lbs	
UV Resistance Abrasion Hydrostatic Puncture Strength Tear Strength	n/a n/a n/a ASTM D751 ASTM D1004 (mod)	n/a n/a n/a 35 lbs 50 lbs warp, 30 lbs fill	

KU

	Color	<b>Cooley Brite SKU</b>	Cooley Brite II SKU
2108	Green	83-2108	83-C2108
2114	Dark Blue	83-2114	83-C2114
2119	Orange	83-2119	83-C2119
2146	lvory	83-2146	83-C2146
2283	Dark Red	83-2283	83-C2283
2648	Light Blue	83-2648	83-C2648
2662	Light Red	83-2662	83-C2662
4048	Forest Green	83-4048	83-C4048
5019	Teal	83-5019	83-C5019
5025	Reflex Blue	83-5025	83-C5025

# LOW MINIMUMS ~ NO MORE COMMON CARRIERS!

Order a few yards or by the roll! NEPCO delivers your awning materials with the lowest minimums in the Northeast!





www.nepcosignsupply.com

# **COOLEY-BRITE<sup>®</sup> LITE**

**TECHNICAL DATA** 

Put-Up (Lengths)

This product also offers and eight year warranty. Cooley-Brite Lite is based on the same proven technology as Cooley-Brite. Cooley-Brite Lite is lighter in weight, **16 oz.**, offering unique flexibility for ease of installation. As with Cooley-Brite it is translucent, flexible, durable and is engineered for high color brilliance and consistent color transparency.

# Additional High Quality, High Performance Fabrics Coming Soon to NEPCO!





Roll Size: 86.5" x 32.81yds

Finished Widths	6'-6"		
Base Fabric / Type	Polyester		
Finish (Coating)	PVC		
Weight	16 oz.		
Mildew Resistant	Yes	Heat Sealable	Yes
Eradicable	Yes	Translucent	Yes
Opaque	No	Fire Resistant	Yes
Limited Warranty	8 years		
Other Uses:	Awning & Sign		

10yds, 25yds & 50yds

SKU	Color	SKU	Color
CBL0606	White	CBL15	Petro Green
CBL1	Cherry Red	CBL16	Intense Blue
CBL10	Black	CBL17	Tangerine
CBL11	Plum Purple	CBL18	Ruby Red
CBL13	Teal	CBL19	Raspberry

Specifications	Test Method	Test Results
UV Resistance	n/a	n/a
Abrasion	n/a	n/a
Hydrostatic	n/a	n/a
Puncture Strength	ASTM D751	35 lbs
Fear Strength	ASTM D1004 (mod)	50 lbs warp, 30 lbs fill
Tensile Strength	ASTM D751-A Grab	215 lbs warp, 145 lbs fill
Shrinkage	ASTM D1204	< 2%
Stretch	n/a	n/a

SKU	Color	SKU	Color
CBL2	Bright Red	CBL5	Navy Blue
CBL20	Sunflower	CBL6	Royal Blue
CBL21	Holly Green	CBL7	Emerald Green
CBL22	Burgundy		
CBL4	Lemon Yellow		





Roll Size: 86.5" x 32.81yds



# 4240-502 Blue (Shown)

**Roll Size:** 86.5" x 32.81yds







**Roll Size:** 84.5" x 32.81yds

**HOLIDAY<sup>®</sup>** 

HOLIDAY is an **12.95oz.** acrylic coated 100% woven polyester flame retardant fabric (600 denier) utilizing a proprietary process to coat both the top and bottom, thus allowing the fabric to be completely reversible. Its Flame Retardant properties allow it to pass California State Fire Marshall, NFPA 701 and CPAI 84 specifications. HOLIDAY, the hottest flame resistant fabric.

Put-Up (Lengths) Finished Widths	45yds & Cut Yardage			Specifications	Test Method	Test Results
Thisned Widths 02			UV Resistance	n/a	n/a	
Base Fabric / Type	100% Woven Polyester Acrylic			Abrasion	n/a	n/a
				<ul> <li>Hydrostatic</li> </ul>	n/a	n/a
Weight				Functure Strength	n/a	n/a
Mildew Resistant	12000 000	Heat Sealable	Yes	Tear Strength	n/a	25 lbs warp, 18 lbs fill
Eradicable			100		n/a	498 lbs warp, 380 lbs fill
~					n/a	n/a
Opaque Limited Warranty			110		n/a	n/a
Limited Warranty Other Uses:	5 years Awning & Marine					

	Color	SKU		Color	SKU		Color	SKU
707	lvory	707-62	740	Hunter Green*	740-62	776	Burgundy*	776-62
710	Royal Blue*	710-62	751	Raven Black	751-62	779	Chocolate Brown	779-62
719	Tan	719-62	765	White	765-62	783	Silver Gray	783-62

10

\*Indicates a Premium Color.





# VALMEX® NAUTICA LIGHT

This fine yarn polyester fabric with single side high quality coating is light weight with a high tear-out force and continued tear-out force resistance. These characteristics are appreciated by boat owners who want to store their tarpaulin without effort in a small space on their boat deck. VALMEX<sup>®</sup> Nautica Light includes a single side PVC coating and a single side special acrylic paint and this optimizes the dirt characteristics and the resistance against decay and it minimizes the maintenance. Please refer to the abartic plant and DVX® Neutron Light is the ideal metric of the the cleaning procedures. VALMEX<sup>®</sup> Nautica Light is the ideal material for applications that need easy handling, optimal protection and handsome impressions such as deck chair and tree tarpaulins, protective covers, removeable sun sails, etc.

Colors: Snow-White, White, Tan, Ivory, Black, Blue, Navy & Gray Special-Order Only Colors: Ocean Green & Silver

# VALMEX® NAUTICA LIGHT (Coated Both Sides)

The PVC coating on both sides and the special acrylic painting of this fine yard polyester fabric permits problem free cleanings of both sides. The advantages of the coating of both sides include, in addition to the good cleaning characteristics, mainly the fact that the material can be sewed as well as welded with all popular welding processes. The special canvas pressing (which makes VALMEX<sup>®</sup> Nautica Light available with a silver color) provides in addition a noble appearance. Due to its coating on both sides, VALMEX<sup>®</sup> Nautica Light both side is especially appreciated for convertible tops or car tops, Bimini tops, sun protection tops, etc.

Colors: Snow-White, White, Tan, Ivory, Black, Blue, Navy/Gray & Gray Special-Order Only Colors: Silver

# VALMEX® NAUTICA HEAVY

This high-strength polyester fabric provides highest tear-out force and continued tear-out force resistance. The characteristics for the longterm use are especially improved by the use of low-wick yarns. The special finish of low-wick yarns prevents water from penetrating the fabric. This reduces mildew to a minimum and bothersome mold stains are a thing of the past. The dirt and cleaning characteristics are further optimized by the application specific PVC coating and the single side painting. The smooth surface pressing provides a noble impression. Due to the high resilience of the fabric and the good material handling, VALMEX<sup>®</sup> Nautica Heavy has an excellent image with boat owners especially for applications that include transport tarpaulins and car tops, convertible tops and access covers.

Colors: White, Tan, Ivory Blue, Navy & Gray

# **VALMEX® NAUTICA LINEN**

The tightly woven polyester fabric has a high quality, single sided PVC coating. The fabric has a weight of 400 g/m<sup>2</sup> and provides high tear-out force and continued tear-out force resistance. VALMEX<sup>®</sup> Nautica Linen is finished single sided with a special paint, which optimizes the dirt characteristics and the resistance against light and weather impacts. The incidence of mildew stains is significantly reduced due to the high quality, anti fungicide finish. In contrast to the other Nautica<sup>®</sup> options, VALMEX<sup>®</sup> Nautica Linen has a noble linen pressing which gives the fabric. Nautica Linen has a noble linen pressing, which gives the fabric a noble structure.

Colors: Blue & Gray



# Image: Construction of the second s

**NEPCO is proud to be affiliated with Recasens USA.** 100% Solution Dyed Acrylic Marine, Awning, Umbrella Fabrics, Waterproof Marine products, PVC coated fabrics, Outdoor Furniture and Shade Screen fabrics.

# Recasens is the leading awning fabric in Europe!

S.A. Recasens is a fifth generation, family owned business founded in 1886. Recasens owns its own spinning, weaving, coating and finishing facilities, as well as offering full service R&D, design and testing services. Recasens USA has built its reputation as a powerful force in the textile industry by manufacturing high performance textiles, including the top rated Recacril<sup>®</sup> 100% solution dyed acrylic marine and awning canvas.

Recasens is the chosen supplier for many leading OEM manufacturers in the Marine and RV industries. Customers include Carefree of Colorado, manufacturer for the global OEM and Aftermarket RV market, and OEM boat companies Stingray, Cobalt, and Rinker power boats and Ameritex Fabric Systems to name a few.

12



# 100% Solution Dyed Acrylic Marine & Awning Fabric

# SUPER TIGHT WEAVE!

Zero shrink and Zero stretch with exceptional water and fade resistance in a full collection of 59 Solids and 79 Stripes.

Limited Five Year Warranty

Available 47", 60" & 98" Rolls

# **COLORS UPDATED IN 2009**

With 59 Solids and 79 stripes in the Recacril<sup>®</sup> Line, Recasens is the company that delivers the styles and colors you want for your Commercial, Residential or Industrial customers and projects.

Proven in Europe, with over 50 years of experience, the Recacril<sup>®</sup> line is perfect for awnings, marine and other outdoor applications. With its tight weave, Recacril<sup>®</sup> provides outstanding water resistance and fabric stability.

NEPCO also offers **Recacril Binding (in 3/4" & 1" TET Bias)** and acrylic braiding to compliment any awning installation. Turn to page 39 for more information!

# **TECHNICAL DATA**

Put-Up (Lengths) Finished Widths	65yds & Cut 47", 60" & 9	0	
Base Fabric / Type	100% Solution Dyed A	acrylics	
Finish (Coating)	Fluorocarbon/Resin		
Weight	9 oz.		
Mildew Resistant	Yes	Heat Sealable	Yes
Eradicable	No	Translucent	No
Opaque	Yes	Fire Resistant	No
Limited Warranty	5 years		
Other Uses:	Awning & Marine		

Specifications	Test Method	Test Results
UV Resistance	AATCC-16	1500+ Hours
Abrasion	ASTM-4157	40,000 Rubs
Hydrostatic	AATCC-127	35 cm
Puncture Strength	ASTM-751	38 lbs
Tear Strength	ASTM-2261	9 lbs warp, 6 lbs fill
Tensile Strength	ASTM D-5034 Grab	255 lbs warp, 156 lbs fill
Shrinkage	5804-100 hours	.4% warp, 0% fill
Stretch	ASTM D-2594	0% warp, 0% fill

# Cut Yardage Available for All Fabrics

# **ENTIRE Recasens Line!** View the complete Recasens catalog online at www.recusacatalog.com

**NEPCO** Carries the

Complete Fabric Swatch Books Available Call for Details





# Acrylic Solids / Standard Colors

SKU	Color	Sizes	SKU	Color	Sizes	SKU	Color	Sizes
R-099	White	47" / 60" / 98"	R-121	Wheat	47″	R-170	Admiral Blue	60″
R-100	Beige	47" / 60"	R-122	Seashell	47″	R-171	Turquoise	47″
R-102	Forest Green	47" / 60" / 98"	R-123	Argenta Grey	47" / 60"	R-172	Blue	47" / 60" / 98"
R-103	Black	47" / 60" / 98"	R-126	Linen	47" / 60"	R-173	Dark Blue	47″
R-104	Chestnut	47" / 60"	R-127	Moonrock	47" / 60"	R-174	Navy Blue	47″ / 60″
R-107	Champagne	47″	R-129	Rye	47" / 60"	R-175	Captain Navy	47" / 60"
R-108	Vanilla	47″	R-133	Desert	47″	R-180	Sand	47″
R-109	Mustard	47″	R-135	Ocean Cruise	60″	R-193	Light Blue	47″
R-110	Lily	47″	R-138	Cadet Grey	47" / 60"	R-195	Cacao	47″
R-111	Camel	47″	R-139	Heather Beige	47 " / 60"	R-199	Atlantic Blue	47" / 60"
R-112	Graphite	47″	R-156	Brown	47" / 60"	R-415	Marble	47″
R-113	Cava	47″	R-158	Oche	47″	R-770	Charcoal Tweed	47" / 60"
R-114	Pearl	47″	R-160	Pistachio	47″	R-771	Green Tweed	60″
R-115	Cream	47″	R-161	Grey	47" / 60"	R-772	Blue Tweed	60″
R-117	Raw	47" / 60" / 98"	R-162	Khaki	47″	R-775	Linen Tweed	47″ / 60
R-118	Pierrot	47″	R-163	Green	47" / 60" / 98"			
R-119	Duna	47″	R-164	Charcoal Grey	47" / 60"			

# **Acrylic Solids / Premium Colors**

SKU	Color	Sizes	SKU	Color	Sizes	SKU	Color	Sizes
R-101	Mandarin	47″	R-176	Red	47" / 60"	R-773	Red Tweed	47" / 60"
R-105	Salmon	47″	R-177	Burgundy	47" / 60" / 98"	R-567	Orange	47" / 60"
R-106	Flamingo	47″	R-182	Vermellon	47" / 60"			
R-130	Wine	47" / 60"	R-554	Yellow	47" / 60"			

# Acrylic Classic & Premium Stripes (Available in 47" Only)

SKU	Color	SKU	Color	SKU	Color	SKU	Color
R-012	Red / White	R-058	Gold / Brown	R-223	Tan / Black	R-810	Baeza
R-014	Green / White	R-061	Gray / White	R-252	Vanilla / Beige	R-821	Deba
R-016	Blue / White	R-144	Green / Light Green	R-630	Tan / Beige	R-825	Jerez
R-017	Black / White	R-166	Blue / Light Blue	R-724	Elda	R-830	Forest / White
R-055	Yellow / White	R-206	Brown / Light	R-742	Sarria	R-876	Galdana
R-056	Brown / White	R-211	Brown / Beige	R-801	Salou		

## Fantasia Stripes (Available in 47" Only)

SKU	Color	SKU	Color
R-4008	Jaca	R-459	Vic
R-412	Motril	R-463	Medina
R-413	Bermeo	R-465	Grecia
R-416	Nerja	R-466	Siria
R-419	Ronda	R-467	Alfaro
R-422	Mojacar	R-468	Corella
R-423	Cambrils	R-501	Blanes
R-425	Luarca	R-510	Cunit
R-430	Bara	R-700	Antilla
R-434	Dalias	R-701	Vecla
R-441	Aran	R-707	Altaful
R-445	Tona	R-708	Lorca
R-448	Najera	R-747	Begur





SKU	Color	SKU	Color
R-803	Alcira	R-874	Llivia
R-804	Merida	R-924	Altaful
R-807	Nijar	R-960	Almen
R-808	Orotava	R-965	Requena
R-812	Inca	R-966	Sagun
R-835	Pravia	R-967	Zorit
R-837	Montrico	R-969	Valdes
R-841	Alcudia	R-970	Valdun
R-842	Tudela	R-971	Truji
R-843	Breda	R-975	Barbat
R-848	Laredo	R-977	PuertoBanus
R-849	Palamos	R-979	Chicla
R-854	Jumilla	R-980	Agua



# Additional High Quality, High Performance Recasens Fabrics From NEPCO!



Roll Size: 60" x 65yds

# RW-172 Blue (Shown)

# **RECWATER WATERPROOF ACRYLIC**

Recwater<sup>®</sup> is a **17.4 oz**, waterproof product line that combines Recacril 100 percent solution-dyed acrylic with a PVC coating to create a material that resists weather, fading and shrinking. Recwater is **available in 10 colors** for automotive, marine, and other outdoor applications. Recwater comes in 60-inch finished widths.

**Colors:** Black, Tan, Moonrock, Gray, Blue, Navy Blue, Atlantic Blue, Green Tweed, Blue Tweed & Red Tweed



R-7121 Wheat (Shown)

R-5000 Solid White

(Shown)

Roll Size: 54" x 65yds

# **DECORLINE FURNITURE FABRIC**

Recacril Decorline<sup>®</sup> furniture fabric is an **80z**., furniture grade, 100 percent solution-dyed acrylic. **Available in 19 solid colors and six patterns**, this 54-inch fabric is used on marine or outdoor furniture cushions. Decorline is highly resistant to fading, tearing, stains and weather.

**Colors:** White, Beige, Forest Green, Black, Chestnut, Champagne, Cream, Raw, Aguamar, Wheat, Linen, Bird's Eye, Green, Turquoise, Navy Blue, Sand, Light Blue, Yellow & Inca

**Patterns:** Repeat 2" (Two Patterns), Repeat 1" (Two Patterns) & Repeat 2.5" (Two Patterns)

# **RECSCREEN SHADE SCREEN**

RecScreen<sup>\*</sup> polyester shade screen filters UV rays and improves air circulation. RecScreen's **antibacterial**, **lead-free coating and fireretardant characteristics** provide additional value to the environmentally conscious consumer. RecScreen's 118-inch width is unique in the industry, making it highly efficient during production and adaptable for a variety of applications in the shade screen product marketplace. Each type of screen has a different tolerance of the weave. Recscreen 4000P has 1% openness of the weave; RecScreen 5000P has 5.5% openness of the weave and RecScreen 6000P has a 3% openness of the weave.

**4000P Patterns:** White, White/Linen, White/Sable, White/Pearl, White/ Charcoal, White/Vanilla, Linen, Black & Black/Bronze

**5000P Patterns:** Solid White, White/Linen, White/Sable, White/Pearl, White/Charcoal, White/Cream, White/Bronze, Solid Black, Black/Charcoal & Black/Vanilla

**6000P Patterns:** Solid White, White/Linen, White/Pearl, Solid Sable, Sable/Pearl, Sable/Charcoal, Solid Black, Black/Bronze, Solid Pearl, Pearl/Linen, Solid Charcoal, Charcoal/Vanilla & Solid Vanilla

# SEAQUEST Marine Upholstery Vinyl

Nassimi's brand line of team performance fabrics, introduces Seaquest - A **32oz**. Marine Upholstery Vinyl. The Seaquest Line is part of a collection of performance engineered vinyls for Contract Furniture, Marine Upholstery, and other seating applications that require superior material strength and high-durability. Each product is engineered to exceed the specific demands of the application, for example in flame resistance, stain resistance, anti-bacterial and anti-microbial protection, UV-resistance, or cold crack.

# **TECHNICAL DATA**

Put-Up (Lengths)	Flat: 40yds & Pleated: 10yd	c Cut Yardage ds. 15vds & Cut Ya	rdage			
Finished Widths	54"	,	8-	Specifications	Test Method	Test Results
				UV Resistance	ASTM G26-96	1,000 Hours
Base Fabric / Type	100% Polyester Knit			Abrasion	ASTM D-4157-92	175,000+ Rubs
Finish (Coating)	n/a			Hydrostatic	n/a	n/a
Weight	32oz.			Puncture Strength	n/a	n/a
Mildew Resistant	Yes	Heat Sealable	n/a	Tear Strength	ASTM D5733-95	25.8 lbs warp, 27.7 lbs fill
Eradicable	No	Translucent	No	Tensile Strength	ASTM D751-98	89.2 lbs warp, 102.7 lbs fill
Opaque	No	Fire Resistant	Yes	Shrinkage	n/a	n/a
Limited Warranty	n/a			Stretch	n/a	n/a
Other Uses:	Marine					

	Color	Flat SKU	Pleated SKU
001	American Beauty	S-001-PSQ	S-001-PSP
002	Anchor	S-002-PSQ	S-002-PSP
003	Buff	S-003-PSQ	S-003-PSP
004	Chalk	S-004-PSQ	S-004-PSP
005	Cove	S-005-PSQ	S-005-PSP
006	Dune	S-006-PSQ	S-006-PSP
007	Ebony	S-007-PSQ	S-007-PSP
008	Emerald	S-008-PSQ	S-008-PSP
009	Forest	S-009-PSQ	S-009-PSP
010	Hampton	S-010-PSQ	S-010-PSP
011	Havasu	S-011-PSQ	S-011-PSP
012	Lemon Peel	S-012-PSQ	S-012-PSP
013	Lighthouse Red	S-013-PSQ	S-013-PSP
014	Lotion	S-014-PSQ	S-014-PSP
015	Marble	S-015-PSQ	S-015-PSP
016	Midnight	S-016-PSQ	S-016-PSP
017	Mist	S-017-PSQ	S-017-PSP
018	Navel	S-018-PSQ	S-018-PSP

# **COMING SOON! - SUNSURE® PLUS** Synthetic Mesh Fabric

Twitchell's SUNSURE® PLUS is a durable yet versatile option for any outdoor application that requires an enhanced level of FR performance. As with other Textiline® brand synthetic fabrics, SUNSURE® PLUS fabrics are comprised of the same PVC coated polyester yarns that have made the brand a household name worldwide.

Colors: Beige, White, Gray, Alabaster, Black & Navy



**Roll Size:** 118" x 27yds









## ·····

	Color	Flat SKU	Pleated SKU
019	Navy	S-019-PSQ	S-019-PSP
020	Oyster	S-020-PSQ	S-020-PSP
021	Pearl Oyster	S-021-PSQ	S-021-PSP
022	Pelican	S-022-PSQ	S-022-PSP
023	Royal	S-023-PSQ	S-023-PSP
024	Ruby	S-024-PSQ	S-024-PSP
025	Sea White	S-025-PSQ	S-025-PSP
026	Smoke	S-026-PSQ	S-026-PSP
027	Teal	S-027-PSQ	S-027-PSP
029	Too White	S-029-PSQ	S-029-PSP
030	White Ice	S-030-PSQ	S-030-PSP





TSP-9002 Beige (Shown)



Roll Size: 61" x 60yds



# **OSEA EXTRUDED Double Pressed Polished Scratch Resistant**

The O'Sea glass is the newest of Vinyl Window Clear technology. O'Sea has formulated the base compound for maximum UV stability and the press polishing process ensures optimized clarity. The O'Sea coating is specifically engineered to provide a superior scratch resistant barrier without compromising the hand or flexibility of the sheet. This unique chemistry also gives the O'Sea sheet exceptional chemical and stain resistance. O'Sea is manufactured of thermoplastic vinyl material.

SKU	Description	Size
OSEA-5DRUM-040C	Clear Window Vinyl (5 Rolls per Drum)	54″ x 110″ x .040
OSEA-3DRUM-040C	Clear Window Vinyl (3 Rolls per Drum)	54" x 110" x .040

# **REGALITE EXTRUDED Double Pressed Polished Marine Grade Sheets**

Regalite<sup>®</sup> press polished sheets are manufactured of thermoplastic vinyl material with a highly polished finish to form a flexible, press polished sheet. These products offer superb dimensional stability, excellent clarity and weathering capabilities, good RF and heat sealability. Each meets or exceeds the material requirements of the Department of Transportation (DOT) and the American National Standards (ANSI)

SKU	Description	Size
REG-3DRUM-030C	Clear Window Vinyl (3 Sheets Per Drum)	54″ x 110″ x .030
REG-3DRUM-040C	Clear Window Vinyl (3 Sheets Per Drum)	54" x 110" x .040



# **MAKROLON AR** Abrasion-Resistant Window Clear

Abrasion and enhanced UV-resistant polycarbonate sheeting that offers glass-like clarity and hardness, coupled with the impact strength of standard polycarbonate. With its superior glass-like clarity, Makrolon AR offers less distortion compared to other marine clears and has 250 times the strength of standard float glass. Its also scratch-resistant coated on two-sides and is highly UV / yellow resistant. Makrolon AR comes with a 5 Year Weathering Warranty and a 10 Year Breakage Warranty.

**Easily Sewn Using Standard Equipment!** .040" and .060" Makrolon AR can be sewn using a diamond-tipped needle. Depending on the thread gauge, you may be able to use a #23 or #24 needle. Its been succesfully sewn with a V-138 thread using a #23 needle. Its also recommended to use a very sharp needle and a new needle is recommended for each job.

SKU	Description	Size
48/040/CLR/AR2	Clear Window Polycarbonate	44" x 92" x .040
48/060/CLR/AR2	Clear Window Polycarbonate	48″ x 96″ x .060

16





Perfect for Patio/Boat Curtain Enclosures!	• U
• Marine Grade - Mildew Resistant	• -2
• Ultra Clear	• Lo

• Perfect for Patio/Boa • Marine Grade - Mild • Ultra Clear		• UV Stabil • -20°F Col • Low Cohe		NAUTICLEAR
SKU	Description		Size	
72M-54-030-57HR	Marine Grade Extru	ded Vinyl	54" x 19yds x .030	
72M-54-040-42HR	Marine Grade Extru	ded Vinyl	54″ x 14yds x .040	
FIRE RATED EX Super Double Po				
• Perfect for Commerce	cial Patio Enclosures	• Compliant with	n NFPA-701 Fire Rating	• -20°F Cold Crack
with Wind Screen Ap		• UV Stabilized -	1200 UV hrs.	Low Cohesion
Perfect for Tent Wine	dows!	• Non-Phthalate		
ѕки	<b>Description</b> Fire Rated Extruded		<b>Size</b> 54″ x 19yds x .030	
		· 		
<b>GENERAL PUR</b> Super Double Po	POSE CALEND	ERED		
Super Double Po	lisnea Clear			
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> </ul>	cation Fire-Rated is	• Printable • Non-Phthalate		• -10°F Cold Crack
<ul> <li>Perfect for any applic not required!</li> </ul>	cation Fire-Rated is		Size	• -10°F Cold Crack
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> </ul>	cation Fire-Rated is UV hrs. <b>Description</b> General Purpose Ca	Non-Phthalate lendered Vinyl	54" x 30yds x .020	• -10°F Cold Crack
<ul><li>Perfect for any applic not required!</li><li>UV Stabilized - 1000</li></ul>	cation Fire-Rated is UV hrs. <b>Description</b>	Non-Phthalate lendered Vinyl		• -10°F Cold Crack
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> </ul>	cation Fire-Rated is UV hrs. <b>Description</b> General Purpose Ca	Non-Phthalate lendered Vinyl	54" x 30yds x .020	• -10°F Cold Crack
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> </ul>	cation Fire-Rated is 9 UV hrs. <b>Description</b> General Purpose Ca Marine Grade Calen	Non-Phthalate lendered Vinyl	54" x 30yds x .020	• -10°F Cold Crack
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> <li>M20-20-54-29-25</li> <li>VINYL WINDOV</li> <li>Dur IMAR Strataglass OPVC Window Vinyl Network</li> </ul>	cation Fire-Rated is OUV hrs. Description General Purpose Ca Marine Grade Caler	Non-Phthalate lendered Vinyl idered Vinyl mulated to clean, sl bibitors will extended	54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window	• - 10°F Cold Crack
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> <li>M20-20-54-29-25</li> <li>VINYL WINDOV</li> <li>Dur IMAR Strataglass Over Window Vinyl Neilim by minimizing the Dur IMAR Strataglass I Strataglass I Dur IMAR Strataglass I Strataglass I Nindow Material. It creating</li> </ul>	cation Fire-Rated is UV hrs. Description General Purpose Ca Marine Grade Caler WCLEANER Cleaner is uniquely fort ceds. Its Special UV Infr deteriorating effects of Polish is formulated to	• Non-Phthalate lendered Vinyl idered Vinyl dered Vinyl the Sun and is safe safely polish and pr er against the dama	54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window e for everyday use.	<ul> <li>-10°F Cold Crack</li> </ul>
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> <li>M20-20-54-29-25</li> <li>VINYL WINDOV</li> <li>Dur IMAR Strataglass Over Window Vinyl Neilim by minimizing the Dur IMAR Strataglass I Strataglass I Dur IMAR Strataglass I Strataglass I Nindow Material. It creating</li> </ul>	cation Fire-Rated is OUV hrs. Description General Purpose Ca Marine Grade Calen VCLEANER Cleaner is uniquely formeded. Its Special UV Infected UV Infected UV Infected Sector a protective barrier formed to use of the commended to use of the commen	• Non-Phthalate lendered Vinyl idered Vinyl dered Vinyl the Sun and is safe safely polish and pr er against the dama	54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window e for everyday use. rotect all PVC Vinyl	<ul> <li>-10°F Cold Crack</li> </ul>
<ul> <li>Perfect for any applic not required!</li> <li>UV Stabilized - 1000</li> <li>SKU</li> <li>G20-20-54-30-15</li> <li>M20-20-54-29-25</li> <li>VINYL WINDOV</li> <li>Our IMAR Strataglass O CVC Window Vinyl Neilm by minimizing the Dur IMAR Strataglass I Window Material. It creation of the second strataglass I Window Material. It creation of the second strataglass I</li> </ul>	cation Fire-Rated is OUV hrs. Description General Purpose Ca Marine Grade Calen VCLEANER Cleaner is uniquely formeded. Its Special UV Infected UV Infected UV Infected Sector a protective barrier formed to use of the commended to use of the commen	• Non-Phthalate lendered Vinyl idered Vinyl idered Vinyl the Sun and is safe safely polish and pr er against the dama every 2-3 months.	54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window e for everyday use. rotect all PVC Vinyl	<ul> <li>-10°F Cold Crack</li> </ul>

• Marine Grade - Mi	oat Curtain Enclosures! ldew Resistant	• -20°F Col		2
• Ultra Clear		Low Cohe	esion	NAUTICLEAR
SKU	Description		Size	
72M-54-030-57HR 72M-54-040-42HR	Marine Grade Extru Marine Grade Extru	,	54″ x 19yds x .030 54″ x 14yds x .040	
FIRE RATED E Super Double P				
	ercial Patio Enclosures	-	n NFPA-701 Fire Rating	• -20°F Cold Crack
with Wind Screen		• UV Stabilized -	1200 UV hrs.	• Low Cohesion
• Perfect for Tent Wi	ndows!	• Non-Phthalate		
<b>5KU</b> 72F-54-030-57HR	<b>Description</b> Fire Rated Extruded	Vinyl	<b>Size</b> 54″ x 19yds x .030	
• Perfect for any appl not required!	ication Fire-Rated is	• Printable • Non-Phthalate		• -10°F Cold Crack
• Perfect for any appl	olished Clear lication Fire-Rated is	Printable     Non-Phthalate lendered Vinyl	<b>Size</b> 54″ x 30yds x .020 54″ x 29yds x .020	• -10°F Cold Crack
<ul> <li>Super Double P</li> <li>Perfect for any appl not required!</li> <li>UV Stabilized - 100</li> <li>SKU</li> <li>520-20-54-30-15</li> </ul>	<b>olished Clear</b> lication Fire-Rated is 00 UV hrs. <b>Description</b> General Purpose Ca	Printable     Non-Phthalate lendered Vinyl	<b>Size</b> 54″ x 30yds x .020	• -10°F Cold Crack
<ul> <li>Super Double P</li> <li>Perfect for any appl not required!</li> <li>UV Stabilized - 100</li> <li>SKU</li> <li>520-20-54-30-15</li> </ul>	olished Clear lication Fire-Rated is 00 UV hrs. Description General Purpose Ca Marine Grade Caler	Printable     Non-Phthalate lendered Vinyl	<b>Size</b> 54″ x 30yds x .020	• -10°F Cold Crack
<ul> <li>Super Double P</li> <li>Perfect for any appl not required!</li> <li>UV Stabilized - 100</li> <li>UV Stabilized - 100</li> <li>SKU</li> <li>520-20-54-30-15</li> <li>M20-20-54-29-25</li> <li>/INYL WINDO</li> <li>Our IMAR Strataglas: VC Window Vinyl N</li> </ul>	olished Clear lication Fire-Rated is 00 UV hrs. Description General Purpose Ca Marine Grade Caler WCLEANER s Cleaner is uniquely form	Printable     Non-Phthalate     Iendered Vinyl Idered Vinyl mulated to clean, sl ibitors will extended	Size 54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window	• -10°F Cold Crack
<ul> <li>Super Double P</li> <li>Perfect for any appl not required!</li> <li>UV Stabilized - 100</li> <li>UV Stabili</li></ul>	olished Clear lication Fire-Rated is 00 UV hrs. Description General Purpose Ca Marine Grade Caler WCLEANER s Cleaner is uniquely for leeds. Its Special UV Infree deteriorating effects of s Polish is formulated to	• Printable • Non-Phthalate lendered Vinyl idered Vinyl idered Vinyl mulated to clean, sl ibitors will extend the Sun and is safe safely polish and p er against the dama	Size 54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window e for everyday use.	• -10°F Cold Crack
<ul> <li>Super Double P</li> <li>Perfect for any appl not required!</li> <li>UV Stabilized - 100</li> <li>UV Stabili</li></ul>	olished Clear lication Fire-Rated is 00 UV hrs. Description General Purpose Ca Marine Grade Caler WCLEANER s Cleaner is uniquely for Needs. Its Special UV Infra the deteriorating effects of s Polish is formulated to creates a protective barrie . Recommended to use of	• Printable • Non-Phthalate lendered Vinyl idered Vinyl idered Vinyl mulated to clean, sl ibitors will extend the Sun and is safe safely polish and p er against the dama	Size 54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window e for everyday use. rotect all PVC Vinyl	•-10°F Cold Crack
<ul> <li>Super Double P</li> <li>Perfect for any appl not required!</li> <li>UV Stabilized - 100</li> <li>UV Stabili</li></ul>	olished Clear lication Fire-Rated is 00 UV hrs. Description General Purpose Ca Marine Grade Caler WCLEANER s Cleaner is uniquely for Needs. Its Special UV Infra the deteriorating effects of s Polish is formulated to creates a protective barrie . Recommended to use of	• Printable • Non-Phthalate	Size 54" x 30yds x .020 54" x 29yds x .020 hine and protect all your ed the life of your window e for everyday use. rotect all PVC Vinyl	• -10°F Cold Crack

• Marine Grade - Mild • Ultra Clear	t Curtain Enclosures! ew Resistant	• UV Stabi • -20°F Co • Low Coh		NAUTICLEAR <sup>2</sup>
SKU	Description		Size	
72M-54-030-57HR 72M-54-040-42HR	Marine Grade Extru Marine Grade Extru	•	54″ x 19yds x .030 54″ x 14yds x .040	
FIRE RATED EX Super Double Pol	lished Clear			
<ul> <li>Perfect for Commerce with Wind Screen Appendix</li> </ul>	pplications!	Compliant wit     UV Stabilized	h NFPA-701 Fire Rating	<ul><li>-20°F Cold Crack</li><li>Low Cohesion</li></ul>
Perfect for Tent Wind	dows!	Non-Phthalate		• Low Concision
<b>SKU</b> 72F-54-030-57HR	<b>Description</b> Fire Rated Extruded	Vinvl	<b>Size</b> 54″ x 19yds x .030	
• UV Stabilized - 1000	U V 1115.			
	Description		Size	
<b>5KU</b> G20-20-54-30-15		,	54" x 30yds x .020	
• UV Stabilized - 1000 <b>sku</b> G20-20-54-30-15 M20-20-54-29-25	<b>Description</b> General Purpose Ca	,		
<b>SKU</b> G20-20-54-30-15 M20-20-54-29-25	<b>Description</b> General Purpose Ca Marine Grade Caler	,	54" x 30yds x .020	
<b>SKU</b> G20-20-54-30-15 M20-20-54-29-25 <b>/INYL WINDOM</b> Dur IMAR Strataglass (	Description General Purpose Ca Marine Grade Caler V CLEANER Cleaner is uniquely for	dered Vinyl	54" x 30yds x .020	
SKU G20-20-54-30-15 M20-20-54-29-25 //INYL WINDOW Dur IMAR Strataglass C PVC Window Vinyl Ne ilm by minimizing the Dur IMAR Strataglass F Vindow Material. It cre	Description General Purpose Ca Marine Grade Caler VCLEANER Cleaner is uniquely for eds. Its Special UV Inf deteriorating effects of Polish is formulated to eates a protective barrie	mulated to clean, s ibitors will extend the Sun and is saf safely polish and p er against the dam	54" x 30yds x .020 54" x 29yds x .020 shine and protect all your led the life of your window e for everyday use.	
SKU G20-20-54-30-15 M20-20-54-29-25 VINYL WINDOW Dur IMAR Strataglass C PVC Window Vinyl Ne ilm by minimizing the Dur IMAR Strataglass F	Description General Purpose Ca Marine Grade Caler VCLEANER Cleaner is uniquely for eds. Its Special UV Inf deteriorating effects of Polish is formulated to eates a protective barrie Recommended to use of	mulated to clean, s ibitors will extend the Sun and is saf safely polish and p er against the dam	54" x 30yds x .020 54" x 29yds x .020 shine and protect all your led the life of your window e for everyday use.	
SKU G20-20-54-30-15 M20-20-54-29-25 VINYL WINDOW Our IMAR Strataglass C PVC Window Vinyl Ne ilm by minimizing the Our IMAR Strataglass F Window Material. It cre narine environments. F	Description General Purpose Ca Marine Grade Caler VCLEANER Cleaner is uniquely for eds. Its Special UV Inf deteriorating effects of Polish is formulated to eates a protective barrie Recommended to use of	mulated to clean, s ibitors will extend the Sun and is saf safely polish and p er against the dam	54" x 30yds x .020 54" x 29yds x .020 shine and protect all your led the life of your window e for everyday use.	



